

C L A I M S

1. Interface for a lamp operating device (13),
having
- 5 - at least one input-side terminal (1, 2) for the
connection of bus lines or for connection with a button
or switch,
- an evaluation logic (3) for the processing of signals
present at the input-side terminal (1, 2) and for the
10 generation of output-side signals for the control of the
lamp operating device (3) and
- at least one electrical isolation element (4), in order
to electrically decouple the input-side terminal (1, 2)
from the lamp operating device (13),
15 characterized in that,
the evaluation logic (3) is arranged on that side of the
electrical isolation element (4) which is towards the at
least one input-side terminal (1, 2).
- 20 2. Interface according to claim 1,
characterized in that,
the evaluation logic (3) is configured to at least
partially switch off a connected lamp operating device
(13).
- 25 3. Interface according to claim 2,
characterized in that,
the evaluation logic (3) is configured to transmit by
means of the electrical isolation element (4) signals or
30 commands to the connected lamp operating device (13) by
means of which this device is separable from the mains
voltage (15).
4. Interface according to claim 2 or 3,

characterized in that,
the lamp operating device (13) is separable from the
mains by means of a relay or an optocoupler controlled
triac.

5

5. Interface according to any preceding claim,
characterized in that,
the evaluation logic (13) is configured to transmit
setting values to the connected lamp operating device
10 (13) by means of the same and/or by means of a separate
electrical isolation element (4).

6. Interface according to any preceding claim,
characterized in that,
15 the electrical isolation element (4) is configured also
to transmit, in bi-directional manner, signals from a
connected lamp operating device (13) to the input-side
terminals and, if applicable, to a bus connected thereto.

20 7. Interface according to any preceding claim,
characterized in that,
in the idle condition, in which no signals are
transmitted, a high level signal is present at the input-
side terminals, which signal supplies the evaluation
25 logic (3) with energy.

8. Interface according any of claims 1 to 6,
characterized in that,
in the idle condition, in which no signals are
30 transmitted, there is present at the input-side terminals
a low level signal, and the evaluation logic (3) can be
activated by means of a change to a high level signal.

9. Interface for a lamp operating device,

having

- at least one input-side signal terminal (1, 2) for the connection of a bus line or for connection with a button or switch, and

5 - an evaluation logic (3) for the processing of signals present at the at least one input-side terminal (1, 2) and for the generation of output-side signals for the control of the lamp operating device (3), and characterized in that,

10 the evaluation logic (3) has a voltage supply independent of the mains voltage supply of the lamp operating device (13).

10. Interface according to claim 9,

15 characterized in that,

the evaluation logic (3) is supplied with voltage by means of the at least one input-side signal terminal (1, 2).

20 11. Lamp operating device, in particular ballast for a fluorescent tube, having an interface (12) in accordance with any preceding claim.

25 12. Method for the control of a lamp operating device via an interface (12), having the following steps:

- application of bus signals or button/switch signals to at least one input-side terminal (1, 2) of the interface (12),

30 - processing of signals applied at the input-side terminal and generation of output-side signals for the control of the lamp operating device (13), and thereupon

- transmission of the processed control signals by means of an electrical isolation element (4) to the lamp operating device (13).

13. Method according to claim 12,
characterized in that,
by means of the electrical isolation element (4) signals
5 or commands are transmitted to the connected lamp
operating device (13), by means of which this device is
separated from the mains voltage (15).
14. Method according to claim 13,
10 characterized in that,
the lamp operating device (13) is separated from the
mains by means of a relay or an optocoupler controlled
triac.
- 15 15. Method according to any of claims 12 to 14,
characterized in that,
by means of the electrical isolation element (4) setting
values are transmitted to the connected lamp operating
device (13).
- 20 16. Method according to any of claims 12 to 15,
characterized in that,
signals are transmitted from a connected lamp operating
device (13) to the input-side terminals (1, 2) and, if
25 applicable, to a bus connected thereto.
17. Method according to any of claims 12 to 16,
characterized in that,
in the idle condition, in which no signals are
30 transmitted, a high level signal is present at the input-
side terminals (1, 2), which signal supplies the
evaluation logic (3) with energy.
18. Method according to any of claims 12 to 16,

characterized in that,
in the idle condition, in which no signals are
transmitted, a low level signal is present at the input-
side terminals (1, 2) and the evaluation logic (3) is
5 activated by means of a change to a high level signal.